

AGRO TREND SNOWBLOWERS



# SNOWBLOWERS

OWNED BY METCO INC.

**31**  
MODELS

HIGH QUALITY FINISH  
ADJUSTABLE CHUTE DEFLECTOR STANDARD  
HIGH EFFICIENCY FAN  
FORMED STEEL CONSTRUCTION  
SMOOTH OPERATION

# 1000-2000 MODELS

**1000-2000 MODELS** provide power, durability, performance and value. With a heavy-duty auger and large high-speed impeller, they really dig into snow banks. They are manufactured with formed steel construction. Inside welds on blower housing and chute provide added strength and structural integrity.



	COMPACT			STANDARD			
	1048	1054	1060	2060	2066	2072	
SNOWBLOWER SPECIFICATIONS	CUTTING WIDTH (in.)	48	54	60	60	66	72
	CUTTING HEIGHT (in.)	24	24	24	26	26	26
	UNIT WEIGHT (lbs.)	370	380	410	520	540	565
	FAN DIAMETER (in.)	20	20	20	24	24	24
	FAN WIDTH (in.)	6	6	6	7	7	7
	NUMBER OF FAN BLADES	4	4	4	4	4	4
	FAN SHAFT OD. (in.)	1	1	1	1 1/4	1 1/4	1 1/4
	AUGER DIAMETER (in.)	13	13	13	13	13	13
	AUGER SHAFT OD (in.)	1	1	1	1 7/16	1 7/16	1 7/16
	AUGER CHAIN	#50	#50	#50	#60	#60	#60
----- OPTIONAL BOLT ON CUTTING EDGE IN STEEL OR POLY -----							
CHUTE LENGTH (in.)	38	38	38	44	44	44	
CHUTE TURNER	----- OPTIONAL -----						
HYD. TURNER	----- OPTIONAL -----						
ELECTRIC TURNER	----- OPTIONAL -----						
ADJUSTABLE DEFLECTOR	----- STANDARD -----						
HYD. DEFLECTOR	----- OPTIONAL -----						
HITCH CATEGORY	1	1	1	1	1	1	
REC. HP MIN	12	15	18	20	20	30	
REC. HP MAX	20	23	25	35	35	40	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

 <p>HYDRAULIC DEFLECTOR CYLINDER</p>	 <p>MECHANICAL TURNER</p>	 <p>HYDRAULIC TURNER</p>	 <p>ADJUSTABLE SKID SHOE</p>	 <p>ADJUSTABLE POLY SKID SHOE</p>	 <p>ELECTRIC TURNER</p>
---	--	---	--	--	--

OPTIONS



# 3000 MODELS




**3000 MODELS** are designed with an open auger and large center auger paddles, the snow blower cuts through even hard packed snow. Prevents clogging and build up as it funnels the snow from a 45 degree floor to the center chute.

		FARM UTILITY				
		3078	3084	3090 s	3096 s	3096 D
SNOWBLOWER SPECIFICATIONS	CUTTING WIDTH (in.)	78	84	90	96	96
	CUTTING HEIGHT (in.)	30	30	30	30	38
	UNIT WEIGHT (lbs.)	800	815	830	945	1300
	FAN DIAMETER (in.)	26	26	28	28	28
	FAN WIDTH (in.)	8	8	8	8	8
	NUMBER OF FAN BLADES	4	4	4	4	4
	FAN SHAFT OD. (mm)	40 mm	40 mm	40 mm	40 mm	40 mm
	AUGER DIAMETER (in.)	17	17	17	17	17
	AUGER SHAFT OD (in.)	1 7/16	1 7/16	1 7/16	1 7/16	1 7/16
	AUGER CHAIN	#60H	#60H	#60H	#80	#80
----- OPTIONAL BOLT ON CUTTING EDGE IN STEEL OR POLY -----						
	CHUTE LENGTH (in.)	48	48	48	48	48
	MECHANICAL CHUTE TURNER			OPTIONAL		
	HYDRAULIC CHUTE TURNER			OPTIONAL		
	ELECTRIC TURNER			OPTIONAL		
	ADJUSTABLE DEFLECTOR			STANDARD		
	HYD. DEFLECTOR			OPTIONAL		
	HITCH CATEGORY	1-2	1-2	----- 2/QUICK HITCH COMPATIBLE -----		
	REC. HP MIN	35	40	45	70	70
	REC. HP MAX	60	75	80	100	100


SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

## OPTIONS

HYDRAULIC DEFLECTOR CYLINDER



MECHANICAL TURNER



HYDRAULIC TURNER



ADJUSTABLE SKID SHOE




# 4000 MODELS



	HEAVY DUTY				
	4096 D	4096 DC*	4102 S	4102 SC*	
SNOWBLOWER SPECIFICATIONS	CUTTING WIDTH (in.)	96	96	102	102
	CUTTING HEIGHT (in.)	38	38	36	36
	UNIT WEIGHT (lbs.)	1410	1665	1390	1500
	FAN DIAMETER (in.)	30	30	30	30
	FAN WIDTH (in.)	12	12	12	12
	NUMBER OF FAN BLADES	5	5	5	5
	FAN SHAFT OD. (in.)	2	2	2	2
	AUGER DIAMETER (in.)	17	17	17	17
	AUGER SHAFT OD (in.)	1 7/16	1 7/16	1 7/16	1 7/16
	AUGER CHAIN	#80	#80	#80	#80
----- STANDARD BOLT ON CUTTING EDGE AND HARDEN SKID SHOES -----					
CHUTE LENGTH (in.)	50	50	50	50	
HYDRAULIC CHUTE TURNER	----- MUST ORDER ORBITAL MOTOR KIT -----				
ADJUSTER	----- CHOOSE HYDRAULIC OR MANUAL ADJUSTMENT -----				
HITCH CATEGORY	----- 2/3N QUICK HITCH COMPATIBLE -----				
REC. HP MIN	85	85	85	85	
REC. HP MAX	135	135	135	135	
MAX1000 540 RPM 1 3/8"	150	150	150	150	
MAX1000 540 RPM 1 3/4"	225	225	225	225	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



## OPTIONS





**4000 MODELS** series blowers are designed for high horse power tractors in demanding conditions. One-piece blower band and one-piece discharge provide structural strength. Protected auger bearings extend the life of the unit. A high quality paint finish protects against corrosion increasing longevity.

### HEAVY DUTY

4102 D	4102 DC*	4108 SC	4108 D	4108 DC*	4120 DC*
102	102	108	108	108	120
38	38	36	38	38	38
1500	1750	1650	1600	1850	2150
30	30	30	30	30	30
12	12	12	12	12	12
5	5	5	5	5	5
2	2	2	2	2	2
17	17	17	17	17	17
1 7/16	1 7/16	1 7/16	1 7/16	1 7/16	1 7/16
#80	#80	#80	#80	#80	#80
----- STANDARD BOLT ON CUTTING EDGE AND HARDEN SKID SHOES -----					
50	50	50	50	50	50
----- MUST ORDER ORBITAL MOTOR KIT -----					
----- CHOOSE HYDRAULIC OR MANUAL ADJUSTMENT -----					
----- 2/3N QUICK HITCH COMPATIBLE -----					
100	100	100	100	100	100
150	150	150	150	150	150
150	150	150	150	150	150
220	225	225	225	225	225



**\*C-DESIGNATES CONTRACTOR BLOWER, INCLUDES:**

- REINFORCED END PLATES
- AUGER HAS HEAVIER TUBE & MORE PEGS
- DRIFT CUTTERS

# 7000 MODELS


**7000 MODELS** Pull-behind blowers are designed for convenience and operator comfort. These blowers allow forward travel while blowing. This is a very cost effective alternative to a front mount blower. Built from the same time proven components are our regular 3 P.T.H. blowers.



		PULL TYPE					
		7160	7268	7274	7378	7384	7396
SNOWBLOWER SPECIFICATIONS	CUTTING WIDTH (in.)	60	68	74	78	84	96
	CUTTING HEIGHT (in.)	24	24	24	30	30	30
	UNIT WEIGHT (lbs.)	410	475	525	1100	1150	1210
	FAN DIAMETER (in.)	20	24	24	26	26	28
	FAN WIDTH (in.)	6	7	7	8	8	8
	NUMBER OF FAN BLADES	4	4	4	4	4	4
	FAN SHAFT OD. (in.)	1	1¼	1¼	40 mm	40 mm	40 mm
	AUGER DIAMETER (in.)	13	13	13	17	17	17
	AUGER SHAFT OD (in.)	1¼	1⅞	1⅞	1¾	1¾	1¾
	AUGER CHAIN	#50	#60	#60	#80	#80	#80
----- OPTIONAL BOLT ON CUTTING EDGE IN STEEL OR POLY -----							
SNOWBLOWER SPECIFICATIONS	CHUTE LENGTH (in.)	38	38	38	38	48	48
	CHUTE TURNER	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
	HYD. TURNER	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
	ADJUSTABLE DEFLECTOR	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
	HYD. DEFLECTOR	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
	ELECTRIC TURNER	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
	HITCH CATEGORY	1	1	1&2	1&2	2/QUICK HITCH COMPATIBLE	2/QUICK HITCH COMPATIBLE
	REC. HP MIN	18	20	30	35	40	70
	REC. HP MAX	25	35	40	75	75	100

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

HYDRAULIC DEFLECTOR CYLINDER



MECHANICAL TURNER



HYDRAULIC TURNER



## OPTIONS



# SKID STEER MODELS






**SKID STEER MODELS** blowers maximize your time and minimize your investment. Built in Canada and patterned after the time proven Agro Trend 2000 series 3 P.T.H. blowers, these efficient machines will make short work of your heavies snow falls.

- FOUR HYDRAULIC FLOW RANGES
- ELECTRONIC OVER HYDRAULIC
- STANDARD ISO FLAT FACE CONNECTION
- HYDRAULIC VALVE BLOCK
- 45 DEGREE FLOOR
- OPEN AUGER DESIGN
- CAST AUGER BEARINGS
- OVERSIZED CENTRE AUGER PADDLES
- FOUR BLADE FAN
- ONE PIECE FAN HOUSING
- VENTED HOOD
- CHUTE DEFLECTOR
- HYDRAULIC CHUTE TURNER

	AT2060 SS	AT2066 SS	AT2072 SS	3084 SS	
SNOWBLOWER SPECIFICATIONS	CUTTING WIDTH (in.)	60	66	72	84
	CUTTING HEIGHT (in.)	26	26	26	30
	UNIT WEIGHT (lbs.)	550	575	600	815
	FAN DIAMETER (in.)	24	24	24	26
	FAN WIDTH (in.)	7	7	7	8
	FAN SHAFT OD. (in.)	1 1/4	1 1/4	1 1/4	1 1/4
	AUGER DIAMETER (in.)	13	13	13	17
	AUGER BEARING (in.)	1 7/16	1 7/16	1 7/16	
	AUGER CHAIN	#60	#60	#60	#60H
	----- OPTIONAL BOLT ON CUTTING EDGE IN STEEL OR POLY -----				
	CHUTE LENGTH (in.)	44	44	44	48
	CHUTE TURNER	HYDRAULIC (STD)	HYDRAULIC (STD)	HYDRAULIC (STD)	HYDRAULIC (STD)
	DEFLECTOR	HYDRAULIC (STD)	HYDRAULIC (STD)	HYDRAULIC (STD)	HYDRAULIC (OPT)
	SKID SHOES	STANDARD	STANDARD	STANDARD	STANDARD

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

## STANDARD FEATURES





(METCO INC.) 1005 TRIBE RD.,  
WEST MONTROSE, ON N0B 2V0

CONTACT YOUR LOCAL DEALER